


CIRANOVA®
SINCE 1929



HIGH QUALITY WOODCARE PRODUCTS

2017

EN



Ciranova® has been the specialist in development and production of finishing products for parquet, furniture, interior and exterior wood for over 80 years. Thanks to our full range of colours, reactive stains, varnishes and oils, as well as waxes and maintenance products; Ciranova is a lead supplier of wood preservatives for the woodworking industry.

As a proactive company, we are involved in research and development on a daily basis in our own labs, with the most advanced technologies and newest raw materials. High quality products that protect and colour your wood are the logical result of this. For example, we recently brought our latest anti-scratch varnish FORTICO to the market.

Our 1-coat oil UNICO and the invisible impregnation oil OCULTO are also the result of our own research and development.

In addition to our latest products, you can find the complete range of Ciranova in this catalogue. Let yourself be inspired by the many options and colours to give your floor or project the finishing it deserves!



CIRANOVA®

WWW.CIRANOVA.EU



TABLE OF CONTENTS

Ciranova	2	Maintenance varnish	24
Colours	7	Hard Floor Fresh	24
Reactive stains	7	Hard Floor Cleaner	24
Vintage	8	Unicare X-Matt	24
Aquapad	9	Hard Floor Polish	25
Aquavintage 2C	10	Maintenance Kit	25
Oils	11	Maintenance waxes	26
UN1CO	11	Wax Remover	26
Hardwaxoil Magic	12	Liquid Flooring Wax	26
Hardwaxoil	13	Liquid Wax	26
Water-based oils	14	Accessories	27
OCULTO	14	Oil Thinner	27
Ecofix Woodlook	15	Oil Retardant	27
Ecofix	15	Pads	27
Water-based varnishes	16	Liming Paste	27
Fortico 2C Matt - Satin	16	Wood Filler	27
Fortico 2C Natural	16	Wax Sticks	28
Fortico 1C Matt - Satin	17	Wood Filler gel	28
Fortico Sealer	17	Exterior	30
Solvent-based varnishes	18	Degreyer	30
Yacht Varnish	18	Wood Cleaner	30
Parquet Varnish UA	18	Teak Oil	31
Waxes	20	Woodprotector	31
Parquet Wax	20	Ecoprotector	32
Quality Wax	21	Decking Oil	33
Liming Wax	21	Industry and development	34
Maintenance Oil	22	Explanation of icons	35
Maintenance Oil	22		
Parquet Soap	22		
Intensive Cleaner	22		
Oil Refresh	23		
Maintenance Kit	23		





COLOURS


REACTIVE STAINS

Reactive stain is a waterbased, reactive ageing stain based on natural and reactive dyes. Reactive stain is particularly suitable for aging wood types containing tannic acid, such as oak and pine. After drying, the reactive stain can be finished with oil, varnish or floor wax.



- » Reacts with tannin in the wood and ensures unique finishing.
- » Unlimited options combined with coloured oils.
- » Colours can be mixed with each other.

Size:	1L / 5L
Coverage:	10-15 m/litre - 70-100g/m ²
Drying time:	6 hours
Application:	





COLOURS

VINTAGE COLOUR


The Vintage assortment gives your floor an aged Vintage look. The Vintage colours Snow, Drift, Dune, Taupe, Ice and Cemento provide a double effect with just 1 coat. The reactive components ensure a reaction with the tannins in the wood, which creates depth.

The lime provides a weathered, c eruse effect which gives the wood its unique vintage look.



- » Simple aging with just 1 coat.
- » Available in 6 colours.
- » Colours can be mixed with each other.


Size: 1L / 5L
 Coverage: $\pm 20 \text{ m}^2/\text{litre} - \pm 50\text{g}/\text{m}^2$
 Drying time: 6 hours
 Application:




VINTAGE DRIFT 6931




VINTAGE ICE 6933




VINTAGE SNOW 6932



VINTAGE DUNE 6930




VINTAGE CEMENTO 6987



VINTAGE TAUPE 6988

VINTAGE F & S

Vintage F & Vintage S are colour- and scent-free products that provide a smoked finish. Combined with bleach; very rustic and authentic finishes are achieved.



VINTAGE F 6777



VINTAGE S 6776

- » Gives the wood an aged look.
- » Vintage F: weathered grey.
- » Vintage S: smoked brown.

Size: 1L / 5L
 Coverage: $\pm 20 \text{ m}^2/\text{litre} - \pm 50\text{g}/\text{m}^2$
 Drying time: 6 hours
 Application:





COLOURS

AQUAPAD


Aquapad is a water-based pigment stain for the even application of all wood types for interior use. Aquapad is developed in such a way that it can quickly and easily be applied on site with a buffing machine.


If you wish to finish the Aquapad with a water-based varnish or oil, a hardener must be added to the Aquapad.



- » Quick and easy to apply.
- » Provides even colouring that accentuates the wood grain.
- » Can be finished with oil or varnish.
- » Colours can be mixed with each other.

Size: 1L / 5L
 Coverage: 10-15 m²/litre - 70-100g/m²
 Drying time: 3 to 4 hours
 Application:





COLOURS



AQUAVINTAGE 2C

A water-based aging stain to give the wood an aged look in a quick and easy way. Also for use on wood types that do not contain tannin.



- » Positive stain that accentuates the wood grain.
- » Gives the wood depth and a unique texture.

Size: 1L / 5L
 Coverage: 10-15 m²/litre
 Drying time: 12 hours
 Application:





OILS

UN1C0

2-component, 1-coat oil of the newest generation, which uses renewable, natural raw materials. Thanks to the special technology, only one coat needs to be applied.

The combination of oil with hardener ensures quick drying and excellent chemical durability.




- » Colours and protects with just one coat.
- » Ecological – free of volatile organic compounds.
- » Quick-drying.
- » Easy to apply.
- » Great coverage: 50-60m²/litre.
- » Great for both parquet and furniture.

Size: 1 liter + 300 ml hardener
400 ml + 120 ml hardener


Coverage: 50 - 60 m²/litre

Drying time: 24 hours

Application:




CLEAR 7170



NATURAL 7253



NATURAL WHITE 7250



WHITE 7251




EXTRA WHITE 7252




CLOUDS 7262



OLD GREY 7257




CHOCOLAT 7255




ENGLISH BROWN 7371




SMOKE 7597




CHERRY RED 7370




BLACK INK 7261



WENGE 7372



MUD 7373



CASTLE 7374



CONCRETE 7375



OILS

HARDWAXOIL MAGIC

Modified parquet oil with excellent wear-resistance. Good filling properties, natural colour and very good chemical and mechanical durability. Very matt and does not become glossy. The durability can be improved even more by adding a hardener UA.



- » Matt, natural finishing that maintains the natural look of the wood surface.
- » Quick-drying.
- » Excellent chemical durability.
- » Colours can be mixed with each other.

Size: 1L / 5L
 Coverage: 30 -35 m²/liter per coat
 Drying time: natural 6 hours,
 coloured 12 hours

Application:



NATURAL 5510



NATURAL WHITE 5616



WHITE 5617



EXTRA WHITE 5743




GREY 5618



OLD GREY 5719



SMOKED OAK 5890



BLACK 5815

HARDWAXOIL MAGIC SATIN


The satin version of the Hardwax Oil Magic gives the floor a beautiful satin shine. The durability can be improved even more by adding a hardener UA 5% (optional).

- » Natural satin finish.
- » Quick-drying.
- » Excellent chemical durability.

Size: 1L / 5L
 Coverage: 25 - 30 m²/litre per coat
 Drying time: 6 to 8 hours

Application:





OILS

HARDWAXOIL

Quick-drying parquet oil with excellent wear-resistance.
 Good filling and good chemical and mechanical resistance.
 Can be used for various applications, such as floors, stairs,
 furniture and panels.



- » Gives the wood a rustic aspect.
- » Multiple coats increase the gloss level.
- » Easy to apply.
- » Colours can be mixed with each other.

Size: 1L / 5L
 Coverage: 25 - 30 m²/litre per coat
 Drying time: natural 6 hours,
 coloured 12 hours

Application:



NATURAL 5484




NATURAL WHITE 5485



WHITE 5486



EXTRA WHITE 5676




GREY 5495




OLD GREY 5496




SMOKED OAK 2377




BLACK 5582



EFFECT BRONZE 7643
 Precolored with Aquapad BLACK 6464




METALLIC 5574
 Precolored with Aquapad BLACK 6464



DARK GREY 5667



ECRU 5781



LIGHT GREY 5782



SAND 5783



CHERRY 5784



WENGE 5785



WATER-BASED OILS

OCULTO

Invisible, environmentally friendly PU water-based impregnating oil for all interior wood surfaces. The wood keeps its original, untreated look. OCULTO contains a UV-absorber and has anti-slip properties.



- » Invisible finish.
- » The original colour of the wood is maintained.
- » Gloss <5.
- » Anti-slip.



Size:	1L / 5L
Coverage:	10-12 m ² /litre
Dust dry:	after 20 to 30 min
Sandable:	after 2 to 4 hours
Chargeable:	after 24 hours
Application:	

EMISSIONS DANS L'AIR INTERIEUR

EN 717-1, Class E1



WATER-BASED OILS


ECOFIX WOODLOOK

An environmentally friendly, water-based impregnating oil for all interior wood surfaces. Ecofix Woodlook ensures that the wood is bleached a little, so that the natural look is maintained longer.



- » Makes the wood slightly lighter.
- » Can be used as primer under OCULTO or FORTICO.
- » Only suitable for pale wood species.

Size: 1L / 5L
 Coverage: 10 - 12 m²/litre per coat
 Dust dry: after 20 to 30 min
 Sandable: after 4 to 6 hours
 Chargeable: after 24 hours
 Application:




ECOFIX


An environmentally-friendly, water-based impregnating oil for all interior wood surfaces. The wood keeps its original, untreated look.



- » Maintains the natural look of untreated wood.
- » Can be used as primer under OCULTO or FORTICO.

Size: 1L / 5L
 Coverage: 10 - 12 m²/litre per coat
 Dust dry: after 20 to 30 min
 Sandable: after 4 to 6 hours
 Chargeable: after 24 hours
 Application:





WATER-BASED VARNISHES

FORTICO 2C – MATT / SATIN

2 components PU, water-based parquet varnish for parquet and heavy-load-bearing wooden floors. FORTICO 2C is extremely scratch-resistant and does not become shiny. FORTICO 2C has anti-slip properties and is very easy to apply without overlaps or roller marks. FORTICO 2C was developed especially for heavy traffic parquet floors, such as commercial spaces, hotels, restaurants, etc.



- » Extremely scratch-resistant.
- » High abrasion resistance.
- » Doesn't burnish.
- » Anti-scratch technology.

Size:	5L
Coverage:	± 100-130 g/m ² per coat ± 8 -10 m ² /litre per coat
Light chargeable:	after 12 hours
Hardened:	after 8 to 10 days
Application:	

Bfl - S1

EN17-3
SAFETY FOR PETS

EMISSIONS DANS L'AIR INTERIEUR

EN 717-1, Class E1

FORTICO 2C – NATURAL

2 components PU, water-based parquet varnish, for parquet and heavy-load-bearing wooden floors. FORTICO 2C is extremely scratch resistant and does not become shiny. FORTICO 2C has anti-slip properties and is very easy to apply without overlaps or roller marks. FORTICO 2C NATURAL provides an invisible finish.



- » Provides an invisible finish.
- » Extremely scratch-resistant.
- » High abrasion resistance.
- » Doesn't burnish.
- » Anti-scratch technology.

Size:	1L / 5L
Coverage:	± 100-130 g/m ² per coat ± 8 -10 m ² /litre per coat
Light chargeable:	after 12 hours
Hardened:	after 8 to 10 days
Application:	

Bfl - S1

EN17-3
SAFETY FOR PETS

EMISSIONS DANS L'AIR INTERIEUR

EN 717-1, Class E1



WATER-BASED VARNISHES

FORTICO 1C – MATT / SATIN

PU water-based parquet varnish for parquet and heavy -load-bearing wooden floors. FORTICO 1C has an excellent chemical and mechanical durability and was developed with the most innovative technologies. Easy to apply without overlaps or roller marks. FORTICO 1C is for finishing parquet and wooden floors in homes and other places that are subject to normal wear.



- » Extremely scratch resistant.
- » High abrasion resistance.
- » Doesn't burnish.
- » Anti-scratch technology.

Size: 1L / 5L
 Coverage: ± 100-130 g/m² per coat
 ± 8 -10 m²/litre per coat
 Light chargeable: after 12 hours
 Hardened: after 8 to 10 days
 Application:



FORTICO – SEALER

A filling, water-based one-component primer for roller application. FORTICO SEALER can be used as a primer for parquet to finish with varnishes from the FORTICO assortment. SEALER is recommended for places with floor heating, tropical wood types and cork.



- » Prevents side-bonding effect and minimises roughening of the fibre.
- » Recommended for tropical wood species and for places with floor heating.

Size: 1L / 5L
 Coverage: 8 - 12 m²/l
 Coverage: 2 to 3 hours
 Application:








SOLVENT-BASED VARNISHES

YACHT VARNISH

Yacht varnish has a very high gloss, excellent water- and weather-resistance and a high scratch resistance. It is also very elastic. For all wood types that are subjected to heavy weather conditions and still have to maintain their protection and gloss.



- » Extreme protection for exterior wood.
- » Gives the wood a high gloss.
- » Apply in thin coats.




Size:	1L / 5 L
Coverage:	10 - 12 m ² /litre per coat
Dust-free:	after 1 hour
Chargeable:	after 24 hours
Application:	  

PARQUET VARNISH UA

Quick-drying parquet varnish, solvent-based, with very high wear-resistance. Can be finished in 2 or 3 coats. Available in matt, satin and gloss. A hardener can be added (5%) to increase the chemical and mechanical resistance.



- » Parquet varnish for parquet and heavy used wooden floors.

Size:	1L / 5L
Coverage:	± 8 - 10 m ² /litre per coat
Dust-free:	after 1 hour
Recoat after:	after 8 hours
Application:	  





WAXES

FLOORING WAX

Traditional floor wax, based on natural and synthetic waxes for the protection of wooden floors. A siliconized resin guarantees better water resistance.



Size: 1L / 5L
 Coverage: ± 7 -12 m²/litre
 Drying times: ± 30 minutes
 Colours: clear, yellow and brown
 Application:







WAXES

QUALITY WAX

Traditionally manufactured floor wax based on natural raw materials, such as carnauba, candelilla, raw bees wax and Portuguese turpentine oil for the protection of wooden furniture.




ANTIQUE 1353




BROWN 1342




CLEAR 1340



DARK 2434



MAHOGANY 1364



MEDIUM 1351



YELLOW 1337


LIMING WAX

Traditionally manufactured turpentine, floor wax based on natural raw materials, Portuguese turpentine oil and titanium white.




WHITE 0917

Size: 0,5 kg / 1 kg / 5 kg
 Coverage: ± 7 -12 m²/litre
 Drying time: 12 hours (at room temperature)
 Colours: clear, yellow, brown, medium, dark, anti-
 que, mahogany

Application: 

Size: 0,5 kg
 Coverage: ± 7 - 12 m²/litre
 depending on wood type
 Drying time: 12 hours
 Colours: titanium white

Application: 





MAINTENANCE OIL

MAINTENANCE OIL

Universal maintenance oil for refreshing all types of oiled wooden floors. Nourishes your floor and gives your floor extra protection and a new look.



Size: 1L / 5L
 Coverage: 50 m²/litre
 Drying time: 12 hours
 Colours: clear, natural, white, grey and black
 Application: 

FLOORING SOAP

Universal parquet soap based on natural oil for the regular maintenance of oiled floors. Parquet soap cleans and nourishes the floor and provides extra water-resistant protection.




Size: 750ml / 5L
 Coverage: 400 m²/litre
 Drying time: 1 hour
 Colours: white and clear


INTENSIVE CLEANER

Cleans thoroughly oiled floors. Especially for removing stains and soap residue. After use of intensive cleaner it is recommended to treat the surface with maintenance oil.



Size: 750ml
 Coverage: 200 m²/litre
 Drying time: 2 to 4 hours




MAINTENANCE OIL

OIL REFRESH

Colourless maintenance oil in spray canister for the local maintenance of all types of oiled floors.



Size: spray 400ml
Coverage: 50 m²/litre
Drying time: 12 hours


MAINTENANCE KIT

Convenient maintenance kit for the maintenance of all oiled floors.



This kit contains:

- Flooring soap 750ml
- Oil refresh 400ml
- Intensive cleaner 750ml
- Cloths





MAINTENANCE VARNISH

HARD FLOOR FRESH

Water-based and ecological cleaning agent for all types of varnished wooden floors. For regular maintenance. Can also be used for the maintenance of parquet finished with our water-based oils.



Size:	750ml
Coverage:	400 -500 m ² /litre
Drying time:	15 min. at room temperature
Colours:	clear



HARD FLOOR CLEANER

Water-based and environmentally-friendly deep-cleaner. For all types of varnished or lacquered wooden floors. Developed especially for the removal of old layers of polish.



Size:	750ml
Coverage:	200-400 m ² /litre
Drying time:	let it soak in for a few minutes
Colours:	clear



UNICARE X-MATT

Universal matt protection for all matt Ciranova bases + laminate and LVt. Prevents premature wear of the floor surface



Size:	750ml
Coverage:	60-80 m ² /litre
Drying time:	1 hour at room temperature
Colours:	white





MAINTENANCE VARNISH

HARD FLOOR POLISH

Water-based and ecological polish, which provides a protective layer to types of varnished or varnished wooden floors. Available in silky gloss.



Size: 750ml
 Coverage: 60-80 m²/litre
 Drying time: 1 hour at room temperature
 Colours: white




MAINTENANCE KIT

Convenient maintenance kit for the maintenance of all varnished floors.



This kit contains:

- Hard floor Fresh 750ml
- Hard floor Cleaner 750ml
- Hard floor Polish 750 ml





MAINTENANCE WAXES

WAX REMOVER

Easily cleans and removes old layers of floor wax.



Size: 1L / 5L
 Coverage: ± 5 m²/litre
 Drying time: 1 hour
 Colours: clear
 Application:



LIQUID FLOORING WAX

Especially for the maintenance of wax-treated wooden floors, water-resistant and good anti-slip properties.



Size: 1L / 5L
 Coverage: ± 10 m²/litre
 Drying time: 2 hours
 Colours: clear, yellow, brown
 Application:



LIQUID WAX

Traditionally made floor wax based on natural raw materials, such as carnauba, candelilla, African bees wax and Portuguese turpentine oil. This natural wax nourishes your antique furniture and provides a deep gloss.



Size: 1L / 5L
 Coverage: ± 10 m²/litre
 Drying time: 2 hours
 Colours: clear, yellow, brown
 Application:





ACCESSORIES

OIL THINNER

Thinner for solvent-based oils.



Size: 2,5L

OIL RETARDANT

Retardant for solvent-based oils.



Size: 2,5L

PADS

Cleaning pads for application of oil and cleaning floors.



Size: 5 units/box
16" / 41 cm

Colours: white, red, black

LIMING PASTE

Ready to use white paste to ceruse wood with open pores. Available in white or off-white (ref. 5393).



Size: 1 kg
Coverage: \pm 3 - 5 m²/litre
Sandable: 1 hour
Recoatable after: 2 hours
Colours: white, off-white

WOOD FILLER

Natural powder to dilute with water. For filling cracks and other defects in wooden surfaces. Can also be mixed with a water stain to colour the filler.



Size: 1 kg
Drying time: 1 to 8 hours
Colours: light oak





ACCESSORIES

WAX STICKS

Strips of coloured wax, kneadable by hand to fill small holes and defects. Wax sticks has the same expansion coefficient as wood, does not shrink and has excellent adhesion properties.



Size: 10 x 14g / box
 Drying time: immediately dry
 Colours: 38 colours


WOOD FILLER GEL

Filler for filling untreated wood. Wood filler gel is a gel that has to be mixed with fine sanding dust of the wood type being treated.



Size: 1L / 5L
 Sandable: 30 min
 Colours: clear








EXTERIOR

DEGREYER

Degreys exterior wood and gives the wood its original colour again.



» Cleans and refreshes aged garden wood.



Size: 2,5L
 Coverage: 5 to 8 m²/litre per coat
 Drying time: very dependent on temperature
 Application: 

WOODCLEANER

Woodcleaner Ciranova is a product for cleaning and degreasing exterior wood. Woodcleaner can be used both on new wood and on wood that has already been treated. By using Woodcleaner, you will achieve a smooth result when finishing the wood with a Ciranova protection product.



» Cleans and degreases wood.
 » Ensures smooth end result after finish.

Size: 5L
 Coverage: ± 10 m²/litre depending on wood type
 Drying time: very dependent on temperature
 Application:  




EXTERIOR

TEAKOIL

For the protection and maintenance of wooden garden furniture. Enhances and protects from all weather conditions.



- » Penetrates into the wood and does not leave residue.
- » Provides natural protection.


Size:	1L / 5L
Coverage:	10 m ² /litre
Drying time:	10 hours
Application:	

WOODPROTECTOR

Natural oil, suitable for exotic wood types. For wooden patios, garden furniture, decking and garden wood. Nourishes, is water-repellent and moisture-regulating.



- » Impregnation oil to protect and nourish wood.
- » Provides natural protection.

Size:	5L
Coverage:	10 m ² /litre
Drying time:	dust dry: 6 hours, recoatable afte: 24 hours
Application:	



EXTERIOR








ECOPROTECTOR

Water-based protection for your exterior wood. Great for treating vertical and horizontal surfaces. Does not form a film, but penetrates into the wood. Ecoprotector provides a nourishing protection that does not flake off.



- » Provides nourishing protection for exterior wood.
- » Does not flake off.
- » The grey colours are adapted for aging new wood.

Size: 1L / 2,5 L
 Coverage: 10 - 14 m²/litre
 Dust dry: 6 hours
 Chargeable: 12 hours
 Colours: 8 colours
 Application:







EXTERIOR

DECKING OIL

Impregnation oil for the protection and maintenance of all exterior wood. Decking oil has a built-in UV blocker that slows down discolouration of the wood. Decking oil nourishes and protects the wood and provides a water-resistant effect.



- » Easy to apply to all wooden patios and decking.
- » A built-in UV blocker ensures that the wood does not age as fast.

Size:	2,5L
Coverage:	12-15 m ² /litre
Dust dry:	6 hours
Chargeable:	12 hours
Colours:	8 colours
Application:	



INDUSTRY AND DEVELOPMENT

In addition to the Ciranova finishing products for the parquet layer, there is also an extensive assortment of industrial products or industrial application in the wood industry, such as UV oils. These products are distributed under the name Debal Coatings and Ciranova industrial finishes.

Due to the know-how from the industrial finishing products and constant innovations in our own labs,

we have a complete assortment of professional products for all applications on wood for both interior and exterior application.

For more information about our industrial products, please contact our technical department.





ICONS



ECO-label

Product is water-based and environmentally friendly.



A+ label

Product complies with the French standard for volatile organic compounds VOC emissions, emissions of volatile organic components.



AGBB

Product complies with the German standard for volatile organic compounds VOC emissions, emissions of volatile organic components.



EN 71-3 label – toy standard

Product meets the standard for toys, where certain maximum migration limits are tested for certain substances.

EN 717-1, Class E1

EN 717-1, Class E1

Product complies with the standard for Formaldehyde emission.



CLASSIFICATION OF REACTION TO FIRE

Tests in accordance with EN 13501-1.



Buffing machine

Product can be applied perfectly with a cleaning machine.



Brush

Product can be applied perfectly with a brush.



Roller

Product can be applied perfectly with a roller.



Spray gun

Product can be applied perfectly with a spray gun.



CIRANOVA[®]
SINCE 1929



Dealer:

PRODUCED BY DEBAL COATINGS NV
Industrieweg 29 – 8800 Beveren-Roeselare – Belgium
Tel. +32 (0)51 30 11 40 – Fax. +32 (0)51 31 26 48
ciranova@ciranova.be

WWW.CIRANOVA.EU